

MediorNet MetroN

- 19" rack size MetroN mainframe with 2 RU dimension
- Redundant power supplies and fan modules
- Rack-mounting in various positions (connectors at the front / connectors on the rear / recessed to allow cabling from the front)
- 64 ports (port 1...32 capable of 10G / port 33...64 capable of 4.25G)
- Auto-sensing of all ports (4.25G / 10G)
- 2 Ethernet ports plus 1 Config port
- 1 Sync Input / 2 Sync Outputs
- **Dual Power Supply**




Status LEDs

	off	green	orange	red	
Link Status	No SFP present	SFP present,	SFP present,	Link active,	
left of SFP slot	No 3FF present	link up	link down	SFP RX power error	
Link Activity	No connection	Connections present and OK		Connections present and damaged	
right of SFP slot both LEDs					
only temporarily		New SFP inserted		Unsupported SFP	
after SFP insertion					

Overall

Environmental Temperature	-5 °C to +40 °C (Non-condensing)		
Supply Voltage	100 240 VAC, 50 / 60 Hz		
Power Consumption	175 W (typically)		
Cooling	4 Redundant Speed Controlled Fans		
Dimensions (w×h×d)	445 mm × 88 mm × 320 mm	including mounting ears	483 mm (19") × 88 mm (2RU) × 425 mm
Weight	12.5 kg (including FANs and PSUs)		



- 1) Link Status LEDs
- Link Activity LEDs
- Link Status LED 1 ... 16
- Link Activity LED 17 ... 32
- Display
- Incremental Encoder 6)
- 7) Link Ports
- Link Status LED 33 ... 48

- Link Activity LED 49 ... 64
- Status LEDs
- **Dual Power Connector**
- 12) Fans